

Rittal – The System.

Faster – better – everywhere.

► Wall-Mounted Housing WM Stainless steel – WM 8017.626

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wall-Mounted Housing WM Stainless steel – WM 8017.626 - WM483612N6



Product description

Material: Door: Stainless steel, all-round foamed-in PU seal
Housing and door: Stainless steel 1.4404 (AISI 316L)
Mounting plate: Carbon steel, zinc-plated

Surface finish: Brushed

**Protection category
IP to IEC 60 529:** IP 66

**Protection category
NEMA:** NEMA 4X

Supply includes: Housing with door(s)
Left hand hinge
Mounting plate
Wall mounting blind-nuts

Packaging unit: 1 pc(s).

Product features

Dimensions: Height: 1200 mm (47 ")
Width: 900 mm (35 ")
Depth: 300 mm (12 ")

Mounting plate: Height: 1155 mm (45 ")
Width: 840 mm (33 ")

86 kg (189.6 lb.)

Approvals

Approvals:  [UL + C-UL \(US\)](#)

Downloads

Documentation:  [Info sheet \(US\)](#)
 [Load brochure \(US\)](#)

2015 © Rittal Corporation