

Rittal – The System.

Faster – better – everywhere.

► Wall-Mounted Housing WM Stainless steel – WM 9851.502

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wall-Mounted Housing WM Stainless steel – WM 9851.502 - WM242010N43PT



Product description

Material: Door: Stainless steel, all-round foamed-in PU seal
Housing and door: Stainless steel 1.4301 (AISI 304)
Mounting plate: Carbon steel, zinc-plated

Surface finish: Brushed

**Protection category
IP to IEC 60 529:** IP 66

**Protection category
NEMA:** NEMA 4X

Supply includes: Housing with door(s)
Left hand hinge
Mounting plate
Wall mounting blind-nuts

Packaging unit: 1 pc(s).

Product features

Dimensions: Height: 600 mm (24 ")
Width: 500 mm (20 ")
Depth: 250 mm (9.8 ")

Mounting plate: Height: 570 mm (22 ")
Width: 449 mm (18 ")

22 kg (48.5 lb.)

Approvals

Approvals:  [UL + C-UL \(US\)](#)

Downloads

Documentation:  [Info sheet \(US\)](#)
 [Load brochure \(US\)](#)

2015 © Rittal Corporation