

# Rittal – The System.

Faster – better – everywhere.

## ► Wall-Mounted Housing WM Stainless steel – WM 9851.506

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Wall-Mounted Housing WM Stainless steel – WM 9851.506 - WM302412N43PT



## Product description

**Material:** Door: Stainless steel, all-round foamed-in PU seal  
Housing and door: Stainless steel 1.4301 (AISI 304)  
Mounting plate: Carbon steel, zinc-plated

**Surface finish:** Brushed

**Protection category  
IP to IEC 60 529:** IP 66

**Protection category  
NEMA:** NEMA 4X

**Supply includes:** Housing with door(s)  
Left hand hinge  
Mounting plate  
Wall mounting blind-nuts

**Packaging unit:** 1 pc(s).

## Product features

**Dimensions:** Height: 760 mm ( 30 " )  
Width: 600 mm ( 24 " )  
Depth: 300 mm ( 12 " )

**Mounting plate:** Height: 730 mm ( 29 " )  
Width: 549 mm ( 22 " )

35 kg ( 77.2 lb. )

## Approvals

---

Approvals:  [UL + C-UL \(US\)](#)

---

## Downloads

---

Documentation:  [Info sheet \(US\)](#)  
 [Load brochure \(US\)](#)

---

2015 © Rittal Corporation