

Rittal – The System.

Faster – better – everywhere.

► Wall-Mounted Housing WM Stainless steel – WM 9851.516

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wall-Mounted Housing WM Stainless steel – WM 9851.516 - WM302408N63PT



Product description

Material: Door: Stainless steel, all-round foamed-in PU seal
Housing and door: Stainless steel 1.4404 (AISI 316L)
Mounting plate: Carbon steel, zinc-plated

Surface finish: Brushed

**Protection category
IP to IEC 60 529:** IP 66

**Protection category
NEMA:** NEMA 4X

Supply includes: Housing with door(s)
Left hand hinge
Mounting plate
Wall mounting blind-nuts

Packaging unit: 1 pc(s).

Product features

Dimensions: Height: 760 mm (30 ")
Width: 600 mm (24 ")
Depth: 210 mm (8.3 ")

Mounting plate: Height: 730 mm (29 ")
Width: 549 mm (22 ")

32 kg (70.5 lb.)

Approvals

Approvals:  [UL + C-UL \(US\)](#)

Downloads

Documentation:  [Info sheet \(US\)](#)
 [Load brochure \(US\)](#)

2015 © Rittal Corporation