

Rittal – The System.

Faster – better – everywhere.

► TopTherm Chillers – the new generation



Rittal TopTherm chillers feature the latest internal technology to deliver better performance to meet the challenges of the 21st century.

These chillers benefit from the latest advances in thermodynamic efficiency, most readily apparent in the repositioning of the unit's condenser fan. Based on proven Rittal modular designs, these chillers can be customized to fit your specific requirements – and provide cooling capacity from 30,000 to 150,000 BTU.

These models provide high efficiency and a level of cooling you've come to expect from Rittal on a footprint that is only 24 inches deep.

Available options to customize your application:

- Hot gas bypass control in the cooling circuit
- More powerful pump(s)
- Water level switch
- Circuit free from non-ferrous metals
- Flow monitor
- Stainless steel enclosures
- Water-cooled condenser
- Ambient temperature control
- Automatic bypass (internal or external)
- Harting connector
- 24 V DC control voltage
- UL electrical components
- Special spray finish—custom RAL colors
- Ability to be used outdoors
- Metal filter mat

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

www.rittal.us



Advantages

- Modular design
- Small footprint
- Convenient servicing
- High reliability thanks to icing protection
- Dual frequencies for international compatibility
- Base platform readily available from stock

Temperature control:

- Microcontroller control (factory setting +18°C, differential value control also possible)

Color:

- RAL 7035

Protection category IP to

IEC 60 529:

- IP 44 (electrics)

Supply includes:

- Complete unit with side panels and door ready for connection
- Multilingual documentation including functional diagram and wiring plans

Note:

- For 3335.880 and 3335.890, two metal filters are required

Characteristic curves of pump:

Available on the Internet

Approvals:

Available on the Internet

Technical details:

Available on the Internet

Power category 27297—54594 BTU (8000—16000 W)

Model No.	3335.790	3335.830	3335.840	3335.850	3335.860	3335.870	3335.880	3335.890
Total cooling output at Tw = 50°F/Tu = 90°F BTU (kW)	22179/25591 (6.5/7.5)	22179/25591 (6.5/7.5)	35145/38557 (10.3/11.3)	47088/51865 (13.8/15.2)	56642/63807 (16.6/18.7)	70973/ 81209 (20.8/23.8)	92128/103729 (27/30.4)	110895/127955 (32.5/37.5)
Total cooling output at Tw = 64°F/Tu = 90°F BTU (kW)	27297/29344 (8/8.6)	27297/29344 (8/8.6)	40946/44699 (12/13.1)	54594/60054 (16/17.6)	68243/74385 (20/21.8)	85304/94175 (25/27.6)	109189/120107 (32/35.2)	136486/150134 (40/44)
Rated power Pel 50/60 Hz BTU (kW)	14911/17777 (4.37/5.21)	14911/17777 (4.37/5.21)	22520/26478 (6.6/7.76)	24909/31392 (7.3/9.2)	31392/40946 (9.2/12)	38898/47429 (11.4/13.9)	51012/60054 (14.95/17.6)	61111/78820 (17.91/23.1)
Rated operating voltage V, ~, Hz	400, 3~, 50 460, 3~, 60	400, 3~, 50 460, 3~, 60	400, 3~, 50 460, 3~, 60	400, 3~, 50 460, 3~, 60	400, 3~, 50 460, 3~, 60	400, 3~, 50 460, 3~, 60	400, 3~, 50 460, 3~, 60	400, 3~, 50 460, 3~, 60
Height inches (mm)	67 (1700)	83 (2100)	84 (2140)	84 (2140)	84 (2140)	84 (2140)	84 (2140)	84 (2140)
Width inches (mm)	32 (805)	32 (805)	32 (805)	32 (805)	47 (1205)	47 (1205)	63 (1605)	95 (2405)
Depth inches (mm)	24 (605)	24 (605)	24 (605)	24 (605)	24 (605)	24 (605)	24 (605)	24 (605)
Rated current max. A	8.2/7.7	8.2/7.7	10/11.4	12.7/13.3	20.1/17.3	22.8/23.8	26.3/26.7	38.4/32.7
Operating temperature range	+50°F...+109°F	+50°F...+109°F	+50°F...+109°F	+50°F...+109°F	+50°F...+109°F	+50°F...+109°F	+50°F...+109°F	+50°F...+109°F
Refrigerant	R410a	R410a	R410a	R410a	R410a	R410a	R410a	R410a
Water connection	1" internal thread	■	■	■	■	■	■	–
	1 1/4" internal thread	–	–	–	–	–	■	■
Temperature hysteresis	+/- 2 K	+/- 2 K	+/- 2 K	+/- 2 K	+/- 2 K	+/- 2 K	+/- 2 K	+/- 2 K
Liquid temperature	+50°F...+77°F	+50°F...+77°F	+50°F...+77°F	+50°F...+77°F	+50°F...+77°F	+50°F...+77°F	+50°F...+77°F	+50°F...+77°F
Tank capacity gal (l)	19.8 (75)	19.8 (75)	19.8 (75)	19.8 (75)	39.6 (150)	39.6 (150)	19.8 (75)	39.6 (150)
Weight lb (kg)	546.7 (248.0)	546.7 (248.0)	621.7 (282.0)	621.7 (282.0)	793.7 (360.0)	824.5 (374.0)	1126.6 (511.0)	1424.2 (646.0)



From Rittal's newest Blue e+ energy efficient air conditioners to our liquid cooling units, enclosure heaters and climate control accessories, scan this qr code and discover the world of Rittal climate control products.

Rittal Corporation

Woodfield Corporate Center
425 North Martingale Road, Suite 400 • Schaumburg, Illinois 60173 • USA
Phone: 937-399-0500 • Toll-free: 800-477-4000
Email: rittal@rittal.us • Online: www.rittal.us

Rittal Systems Ltd.

6485 Ordan Drive • Mississauga, Ontario L5T 1X2 • Canada
Phone: 905-795-0777 • Toll-free: 800-399-0748
E-Mail: marketing@rittal.ca • Online: www.rittal.ca

Rittal Mexico

Dr. Roberto Gayol 1219-1B • Col. Del Valle Sur, 03100 • Mexico, D.F.
Phone: (+52) (55) 5559-5369 • Toll-free: 01 800 8 Rittal (748.825)
E-Mail: info@rittal.com.mx • Website: www.rittal.com.mx

